

## Seat Belts for Forklift

Seat Belt for Forklift - Described in the Regulation guidelines are the use of operative restraints and seatbelts on forklifts. It states that the liability falls on the employers' to be able to make certain that every machinery, piece of equipment and tool is utilized correctly according to the directions of the manufacturer.

Rough Terrain lift trucks have to meet the guidelines of ANSI Standard ASME B56.6-1992 with regards to their use, design, maintenance, inspection and fabrication.

Side boom tractors and mobile machinery with a Rollover Protective Structure, or ROPS for short, need to contain seat belts that satisfy the requirements of the Society of Automotive Engineers, or SAE, Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If whatever mobile equipment has seat belts required by law, the driver and subsequent passengers should make sure they use the belts each time the motor vehicle is in motion or engaged in operation for the reason that this could cause the equipment to become unbalanced and thus, not safe.

If a seat belt or various operator restraint is required on a lift truck.

While operating a forklift, the seat belt requirements will depend on a number of factors. Contributing factors to this determination may include whether or not the forklift is outfitted with a Rollover Protective Structure, the kind of forklift itself and the year the forklift was actually manufactured. The manufacturer's instructions and the requirements of the applicable standard are referenced in the Regulation.

With regards to a driver restraint device, enclosure or system, ANSI Standard ASME B56.1-1993 with regards to powered industrial trucks, is intended to aid the operator in reducing the possibility of entrapment of the torso and/or head between the truck and the ground in the event of a tip over. The restraint device or system might comprise a seat belt, while a seat belt is not essentially a part of such equipment or system.